



- Cover : Yellow/Green/Black cover slight abrasion and weather resistant compound
 Reinforcement : High tensile wire helix embedded between layers of nylon cord
 Tube : Black NR/SBR rubber compound hose for water
 Application : A heavy duty wire reinforced rubber suction hose construction, quarries and general use
 Temperature range -35°C to +80°C (-30°F to +180°F)
 Branding : Flexy

Part No.	ID x OD		Max. Work Pressure (PSI)	Burst Pressure (PSI)	Standard Length (M)
	inch	mm			
WSB - 100	1.00 x 1.42	25 x 36	300	900	60
WSB - 150	1.50 x 1.93	38 x 49	300	900	60
WSB - 200	2.00 x 2.50	51 x 63	300	900	60
WSB - 250	2.50 x 3.03	63 x 77	300	900	60
WSB - 300	3.00 x 3.63	76 x 92	300	900	60
WSB - 400	4.00 x 4.65	102 x 116	300	900	60
WSB - 500	5.00 x 5.67	127 x 144	300	900	40
WSB - 600	6.00 x 6.73	152 x 171	300	900	30
WSB - 800	8.00 x 8.86	203 x 225	300	900	30
WSB - 1000	10.00 x 11.02	254 x 280	300	900	12
WSB - 1200	12.00 x 13.00	305 x 330	300	900	12